



EXPII
TECHNOLOGIES

YOUR WORLD IS MORE SECURE WITH US



EXP-10016CXH

5 MP 16 CHANNEL XVR



BUY 16 CHANNELS,
WATCH 20 CHANNELS





EXP-10016CXH

5MP 16 CHANNEL XVR

EXPILL TECHNOLOGIES

Specifications:

Inputs	16Mbps ~32 Mbps, IP Bandwidth default is 8Mbps,
out	64Mbps
Analog video -input	16CH inputs
IP Video Input	4ch, (only IP up to 20ch)
Composite Video Input	up to 20 ch (Analog video + IP video)
Compression	Audio: G.711a; Video: H.264/H.265
Display resolution	Analog :5MP -Lite (1280*1944): 12fps;1080N/720P/960H IP :1080P/720P
Speed	Analog :5MP -Lite (1280*1944): 12 fps (each ch)1080 N (960*1080) :15fps (each ch);720P:15fps (each ch) IP: PAL:25 fps (each ch) / NTSC: 30fps (each ch)
Event	MD (Sensitivity Level 1~8)
	Video loss Beep,
	Email, Push notification to Mobile APP
Playback function	Fast forward / backward (2x, 4x, 8x,16x) Slow forward (1/2x, 1/4x, 1/8x,1/16x)
Playback	5MPlite:90fps (Max 6CH playback) ;1080P:160fps (Max 8CH playback) ;720P:320fps Max 8CH playback)
BNC	N/A
VGA	N/A
HDMI	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920* 1080, EDID)
Ethernet	1 RJ45 10/100Base -T
USB	USB2.0*2(front)
Audio	N/A
HDD	1 SATA HDD, up to 8TB
RS485	N/A
Alarm Input/out	N/A
Dimension (WxDxH)	300X227X53mm
Input Voltage/Current	DC12V/2A
Power consumption (excluding hard disk)	8W
Operating Temperature/Humidity	Temperature: 0°C~+40°C (32°F ~ 104°F) ,Humidity : Less than 90%RH

Your World is More Secure with us

General Information

- 16 channel Input
- 5MP HD Supported XVR
- TVI/AHD/DVR/IP
- 4 Channel IP (Up To 20 Channels)
- H.264/H.265 Video Compression
- 1 SATA Interface Up-to 8TB Per Interface
- Input/Output Bandwidth 8/64 Mbps

Dimensions

