



**EXPLL**  
TECHNOLOGIES

YOUR WORLD IS MORE SECURE WITH US



# EXP-1004CX4K

8MP 4 CHANNEL XVR



BUY 4 CHANNELS,  
WATCH 6 CHANNELS





# EXP-1004CX4K

## 8MP 4 CHANNEL XVR

### Specifications:

Model	<b>EXP-1004CX4K</b>
Inputs	12Mbps ~36Mbps, IP Bandwidth default is 12Mbps,
out	48Mbps
Analog video -input	4CH inputs
IP Video Input	2ch, (only IP up to 6ch)
Composite Video Input	up to 6ch (Analog video + IP video)
Compression	Audio: G.711a; Video: H.264/H.265
Display resolution	Analog: 8MP (15fps) ,5MP (20fps) ,4MP/1080P/720P/960H 30fps IP: 4K/4MP/1080P/720P
Speed	Analog :8MP:7 fps (each ch),5MP:12 fps (each ch),4MP:15 fps (each ch),1080P:PAL:25 fps (each ch)/NTSC:30fps(each ch) IP:PAL:25fps (each ch)/NTSC: 30fps (each ch)
Event	MD (Sensitivity Level 1~8) Video loss Beep, Email, Push notification to Mobile APP
Playback function	Fast forward / backward (2x, 4x, 8x,16x) Slow forward (1/2x, 1/4x, 1/8x,1/16x)
Playback	8MP: 28fps, 5MP: 48ps, 4MP: 60fps, 1080P: 120fps PID, LCD, PD&VD
BNC	1 (704*576)
VGA	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)
HDMI	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 , 2560*1440, 3840*2160/EDID )
Ethernet	1 RJ45 10/100 Base -T RJ45 100/1000 Base -T
USB	USB2.0*1(front), USB2.0*1+(rear)
Audio	4 in / 1 out
E-sata	1 optional , not supported by default
HDD	1 SATA HDD, up to 8 TB default (Design reserved 2HDD)
RS485	1
Alarm Input/out	4 in /1 out optional, not supported by default
Dimension (WxDxH)	300X227X53mm
Input Voltage/Current	1HDD:DC12V/2A, 2HDD:DC12V/5A
Power consumption (excluding hard disk)	4.7W
Operating Temperature/Humidity	Temperature: 0°C~+40°C (32°F ~ 104°F), Humidity: Less than 90%RH

EXP  
LL  
TECHNOLOGIES

Your World is More  
Secure with us

### General Information

- 4 channel Input
- 4K HD Supported XVR
- TVI/AHD/DVR/IP
- 2 Channel IP (Up To 6 Channels)
- H.264/H.265 Video Compression
- 1 SATA Interface Up-to 8TB Per Interface
- Input/Output Bandwidth 48/12 Mbps

### Dimensions

