



EXPII
TECHNOLOGIES

YOUR WORLD IS MORE SECURE WITH US



EXP-1004CXH1

5MP 4 CHANNEL XVR



BUY 4 CHANNELS,
WATCH 5 CHANNELS





EXP-1004CXH1

5MP 4 CHANNEL XVR

EXP L L T E C H N O L O G I E S

Specifications:

Model	EXP-1004CXH1
Inputs	4Mbps ~20Mbps IP Bandwidth default is 4Mbps, decrease one Analog channel can increase 4Mbps (default decoding performance 1080P 60 fps)
Bandwidth out	32Mbps
Analog video -input	4CH inputs
IP Video Input	1 ch, (only IP up to 5ch)
Composite Video Input	up to 5 Ch (Analog video + IP video)
Installation wizard	Yes
Compression	Audio: G.711a Video: H.264/H.265
Display resolution	Analog :5MP -Lite:20fps 4MP -Lite:30fps 1080P/720P/960H:30fps IP:1080P/720P Single IPchannel preview up to 2MP 30fps multi -channel preview only sub stream
Speed	Analog: 5MP -Lite:20fps (each Ch) 4MP -Lite:30fps (each Ch) 1080P/720P:PAL:25 fps (each Ch)/NTSC:30fps (each Ch) IP: PAL:25fps (each Ch)/NTSC: 30fps (each Ch) Sub-stream Max PAL : 704*576:10 fps (each Ch)/NTSC : 704*480:10 fps (each Ch)
Event	MD (Sensitivity Level 1~8), Video loss Email, Push notification to Mobile APP
Playback Function	Fast forward / backward (2x, 4x, 8x,16x), Slow forward (1/2x, 1/4x, 1/8x,1/16x)
Playback	5MPlite:80 fps 4MPlite: 120 fps 1080 P: 120fps 720P:120fps
UI/Monitoring Local	UI5.0
UI/Monitoring WEB	N/A
Mobile viewer	Pollo Connect
Push Notification	TUTK/RS
P/W Reset	Factory Reset: Press 10 seconds
HDMI	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920* 1080, EDID)
Ethernet	1 RJ45 10/100Base -T
USB	USB2.0*2
HDD	1 SATA HDD, up to 8TB
Input Voltage/Current	DC12V/2A
Power consumption	3.6W
Temperature/Humidity	Temperature: 0°C~+40°C (32°F ~ 104° F) Humidity: Less than 90%RH

Your World is More Secure with us

General Information

- Up to 5 channel(4 Analog Video + 1-IP Video)
- 5MP Resolution
- Factory Reset Button: Press 10 Seconds
- Incoming Bandwidth 32Mbps
- H.264/H.265
- Motion Detection, Video Loss Email, Push Notification to Mobile APP
- 1 SATA Interface Up to 8TB

Dimensions

