



EXPII
TECHNOLOGIES

YOUR WORLD IS MORE SECURE WITH US



EXP-1008CX4K

8MP 8 CHANNEL XVR



BUY 4 CHANNELS,
WATCH 12 CHANNELS





EXP-1008CX4K

8MP 8 CHANNEL XVR

Specifications:

Model	EXP-1008CX4K
Inputs	24Mbps ~72Mbps, IP Bandwidth default is 24Mbps,
out	72Mbps
Analog video-input	8CH inputs
IP Video Input	4ch. (only IP up to 12ch)
Composite Video Input	up to 12ch (Analog video + IP video)
Compression	Audio: G.711a; Video: H.264/H.265
Display resolution	Analog: 8MP (15fps) ,5MP (20fps) ,4MP/1080P/720P/960H 30fps IP: 4K/4MP/1080P/720P
Speed	Analog :8MP:7 fps (each ch), 5MP:12 fps (each ch), 4MP:15 fps (each ch), 1080P:PAL:25 fps (each ch)/NTSC:30fps (each ch) IP:PAL:25 fps (each ch)/NTSC: 30fps (each ch)
Event	MD (Sensitivity Level 1~9) Video loss Beep, Email, Push notification to Mobile APP
Playback function	Fast forward / backward (2x, 4x, 8x,16x) Slow forward (1/2x, 1/4x, 1/8x,1/16x)
Playback	8MP: 60fps (Max 4CH playback) ,5MP: 96fps (Max 8CH playback) 4MP: 120fps (Max 8CH playback) ,1080P: 240fps PID, LCD Factory Reset: Press 10 seconds
BNC	1 (704*576)
VGA	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)
HDMI	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 , 2560*1440, 3840*2160/EDID)
Ethernet	1 RJ45 10/100 Base -T 1 RJ45 100/1000 Base -T
USB	USB2.0*1(front), USB2.0*1+(rear)
Audio	4 in / 1 out (Max 8 in /1 out optional.)
E-sata	1 optional, not supported by default
HDD	1 SATA HDD, up to 8 TB default (Design reserved 2HDD)
RS485	1
Alarm Input/out	8 in /1 out optional, not supported by default
Dimension (WxDxH)	300X227X53mm
Power consumption (excluding hard disk)	11W
Operating Temperature/Humidity	Temperature : 0°C~+40°C (32°F ~ 104°F), Humidity : Less than 90%RH

Your World is More
Secure with us

General Information

- 8 channel Input
- 4K HD Supported XVR
- TVI/AHD/DVR/IP
- 4 Channel IP (Up To 12 Channels)
- H.264/H.265 Video Compression
- 1 SATA Interface Up-to 8TB Per Interface
- Input/Output Bandwidth 24/72 Mbps

Dimensions

