



EXPLL
TECHNOLOGIES

YOUR WORLD IS MORE SECURE WITH US



EXP-1008CXH

5 MP 8 CHANNEL XVR



BUY 8 CHANNELS,
WATCH 10 CHANNELS





EXP-1008CXH

5MP 8 CHANNEL XVR

Specifications:

Model	EXP-1008CXH
Inputs	8Mbps ~40Mbps, IP Bandwidth max is 8Mbps
out	56Mbps
Analog video-input	8CH inputs
IP Video Input	2ch, (only IP up to 10ch)
Composite Video Input	up to 10 ch (Analog video + IP video)
Compression	Audio: G.711a; Video: H.264/H.265
Display resolution	Analog: 5MP-Lite: 12 fps (each ch), 1080 N (960*1080) :30 fps (each ch), 720P:30fps(each ch) IP: PAL:25 fps (each ch) / NTSC: 30fps (each ch)
Speed	Analog: 5MP-Lite (1280*1944): 12 fps (each ch) 1080 P (1920*1080) :15 fps (each ch) 1080 N (960*1080) :30 fps (each ch), 720P:30 fps (each ch) IP: PAL:25fps (each ch)/NTSC: 30fps (each ch)
Event	MD (Sensitivity Level 1~8) Video loss Beep, Email, Push notification to Mobile APP
Playback function	Fast forward / backward (2x, 4x, 8x, 16x) Slow forward (1/2x, 1/4x, 1/8x, 1/16x)
Playback	5MPlite:48fps, 1080P: 60fps, 720P:120 fps (Max 4CH playback)
VGA	N/A
HDMI	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080, EDID)
Ethernet	1 RJ45 10/100Base -T
USB	USB2.0*2(front)
Audio	N/A
HDD	1 SATA HDD, up to 8TB
Alarm Input/out	N/A
Dimension (WxDxH)	230*215*47mm
Input Voltage/Current	DC12V/2A
Power consumption (excluding hard disk)	4W
Operating Temperature/Humidity	Temperature: 0°C~+40°C (32°F ~ 104°F), Humidity : Less than 90%RH

EXPLL TECHNOLOGIES

Your World is More
Secure with us

General Information

- Up to 5 channel(4 Analog Video + 1-IP Video)
- 5MP Resolution
- Factory Reset Button: Press 10 Seconds
- Incoming Bandwidth 32Mbps
- H.264/H.265
- Motion Detection, Video Loss Email, Push Notification to Mobile APP
- 1 SATA Interface Up to 8TB

Dimensions

