



EXPLL
TECHNOLOGIES

YOUR WORLD IS MORE SECURE WITH US



EXP-40BN4MF

4MP Built-In Audio Bullet Camera



1/3"
SENSOR



3.6MM
LENS



2 ARRAY
LED



IR
DISTANCE



INTERNAL
MIC.



4MP



Onvif



H.265+



IP67



PoE





EXP-40BN4MF

4MP Built-In Audio Bullet Camera

Specifications:

Model	EXP-40BN4MF
Imaging Device	1/3"
Effective Pixels	4MP 2560(H)×1440 (V)
Scanning System	Progressive CMOS
Min. Illumination	Colour 0.05lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON
Focal Length (Zoom Ratio)	3.6 mm
Max. Aperture Ratio	F No. 2.3
Angular Field of View	Horizontal: 75°, Vertical:41°, Diagonal: 88°
Min. Object Distance	2m
Lens Type	Fixed(M12)
IR Viewable Length	Up to 30m
Camera Title	On/Off
Day & Night	IR cut filter with auto switch (Day/Night/Auto/Schedule)
Backlight Compensation	Off/On (5 Zone)
Wide Dynamic Range	DWDR
Digital Noise Reduction	3D DNR
Motion Detection	Off/On (8 Level)
Privacy Masking	Off/On (4 Zone, Rectangle)
Gain Control	Auto
White Balance	Auto/Manual
Electronic Shutter Speed	1/5 ~ 1/20000s
On-Board Storage	Micro SD slot, up to 256GB
Audio	Built-in microphone
Ethernet	RJ45(10/100BASE -T)
Video Compression Format	H.265/H.264
Resolution	Mainstream 4MP (2560x1440)/1 -30fps Sub stream VGA (640x480)/1 -30fps
Video Quality Adjustment	12.8Kbps ~ 4Mbps
Bitrate control method	CBR/VBR
Streaming Capability	Main/Sub
IP	IPv4
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, HTTPS
Security	IP address filter; complicated password; Authenticated username and password
Streaming Method	Unicast/Multicast
Application Programming Interface	ONVIF (Profile S/G/T)
Web Viewer	IE8,9,10,11, Chrome 44/lower, Firefox 51/lower, Safari 11/lower
Operating Conditions	-30 ~ +55°C/less than ≤ 95% RH
Storage Conditions	-30 ~ +60°C/less than ≤ 95% RH
Ingress Protection	IP67
Input Voltage / Current	D12V/POE(IEEE802.3af)
Colour / Material	White/Metal
Weight	0.650 Kg

Your World is More
Secure with us

General Information

- Support Built-In Audio
- 30m IR Distance
- IP67
- Support Built-In SD cards Upto 256GB
- H.265/H.264

Dimensions

