



**EXPII**  
TECHNOLOGIES

YOUR WORLD IS MORE SECURE WITH US



# EXP-504XDNP4M

4MP PTZ Network Camera



1/1.8 " SENSOR



4X OPTICAL ZOOM



Built in Mic



PoE+



4MP



360°



H.265



IP67



PLATE RECOGNITION





# EXP-504XDNP4M

## 4MP PTZ Network Camera

### Specifications:

Model Number	<b>EXP-504XDNP4M</b>
Image Sensor	1/1.8" Progressive Scan CMOS
Max Resolution	4MP 2560x1440
Min Illumination	Color: 0.001 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR
Shutter Speed	1/5 s to 1/20000 s
Slow Shutter	Yes
Day & Night	IR cut filter
Zoom	4x optical
Focal Length	2.8 mm to 12 mm
FOV	Horizontal field of view: 114.6° to 48.3° (wide -tele), Vertical field of view: 59° to 27.1° (wide -tele), Diagonal field of view: 141.6° to 55.5° (wide -tele)
Aperture	Max. F1.3
Focus	Auto, manual
Supplement Light Range	IR Distance/Warm light: up to 30m
Supplement Light Type	IR & Warm light
Movement Range (Pan)	350°
Movement Range (Tilt)	0° to 80°
Pan Speed	Pan speed: configurable from 0.6° to 54°/s
Tilt Speed	Tilt speed: configurable from 0.6° to 52°/s
Presets	255 (Pre-set calls have a limit of 20,000 times)
Main Stream	50 Hz: 50 fps (2560x1440, 2304x1296, 1920x1080, 1280x720); 60 Hz: 60 fps (2560x1440, 2304x1296, 1920x1080, 1280x720);
Sub-Stream	50 Hz: 50 fps (1280x720, 640x480, 320x240); 60 Hz: 60 fps (1280x720, 640x480, 320x240);
Third Stream	50 Hz: 50 fps (340x480, 320x240); 60 Hz: 60 fps (340x480, 320x240);
Video Compression	Main stream: H.265+/H.265/H.264+/H.264/MJPEG Sub-stream: H.265+/H.265/H.264+/H.264/MJPEG Third stream: H.265+/H.265/H.264+/H.264
Video Bit Rate	8 kbps to 8192 kbps
H.264 Type	Baseline Profile/Main Profile/High Profile
H.265 Type	Main Profile
Audio Compression	G.711a/G.711u
Protocols	IPv4/IPv6, HTTP, HTTPS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, TCP/IP, UDP, DHCP, PPPoE,
API	Onvif (Profile S, Profile G, Profile T), Http API
Simultaneous	Live View Up to 15 channels
User/Host	5 User
Security	Password protection, complicated password, HTTPS encryption, IP address filter, control timeout settings
Client	Pollo Connect
Web Browser	IE10/11, Safari V12.1 above, Firefox V.52 above, Google chrome V.57 above, Edge V.79 above
Day/Night Switch	Full Color, Day, Night, Auto, Schedule
Image Enhancement	BLC, HLC, 3D DNR
Wide Dynamic Range (WDR)	120 dB
Image Settings	Saturation, brightness, contrast, sharpness, Hue and white balance adjustable by client software or web browser
Privacy	4 privacy masks
Ethernet Interface	1 RJ45 10M/100M self-adaptive Ethernet port
On-Board Storage	Built-in memory card slot, support microSD/SDHC/SDXC card, up to 256 GB
Audio	1 built-in MIC
Reset	Yes
Built-In Speaker	1 built-in speaker
Basic Event	Motion detection
Deep Learning Function	Face Recognition, Human & Vehicle Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Queue Length Detection, License Plate Detection
Alarm Linkage	Upload to FTP, send email, trigger recording, audible warning, lights flashing
Power	DC 12V/POE, max. TBD
Operating Condition	-30 °C to 60 °C (-22 °F to 149 °F), Humidity 90% or less (non-condensing)
Material	Metal
Dimension	Ø 153 mm × 118.8 mm (Ø 6.02" × 4.68")
Weight	Approx. 0.95 kg (2.1lb)
Protection	IP67, IK10

Your World is More Secure with us

### General Information

- 1/1.8" CMOS
- 4X Optical Zoom
- H.264+/H.265+
- Support HLC, BLC & 3D DNR
- 30m Smart IR/Warmlight
- Mainstream 25/30fps
- Face Comparison & Recognition
- Smart Detection (Human, Vehicle, Line Crossing & Perimeter Detection)
- Support SD Card Storage upto 256GB
- Support License Plate Recognition
- IP67 & IK10

### Dimensions

