



**EXPLL**  
TECHNOLOGIES

YOUR WORLD IS MORE SECURE WITH US



# EXP-60BN5MM

5MP Motorized Built-In Audio Bullet Camera



1/2.7"  
SENSOR



2.7-13.5mm  
MOTORIZE LENS



30 SMD  
LED



IR  
DISTANCE



AUDIO  
INPUT OUT



5MP



Onvif



H.265



IP67



PoE





# EXP-60BN5MM

## 5MP Motorized Built-In Audio Bullet Camera

### Specifications:

Model Name	<b>EXP-60BN5MM</b>
Imaging Device	1/2.7"
Effective Pixels	5MP 2592(H)x1944(V)@30fps
Scanning System	Progressive CMOS
Min. Illumination	Color 0.004lux @ F1.6(AGC ON ); B/W 0 lux @ IR ON
Focal Length (Zoom Ratio)	2.7 -13.5mm
Max. Aperture Ratio	F No. 1.8 (W) ~ 3.3(T)
Angular Field of View	Horizontal: 31 ~102°, Vertical: 23 ~ 73°, Diagonal: 38 ~ 138°
Min. Object Distance	0.3m~INF
Lens Type	Manual(Ø14)
IR Viewable Length	Up to 50m
Camera Title	On/Off
Day & Night	IR cut filter with auto switch Day/Night/Auto/Image/Schedule)
Backlight Compensation	Off/On (5 Zone)
Wide Dynamic Range	DWDR
Digital Noise Reduction	3D DNR
Motion Detection	Off/On (8 Level)
Privacy Masking	Off/On (4 Zone, Rectangle)
Gain Control	Auto
White Balance	Auto/Manual
Electronic Shutter Speed	1/5 ~ 1/20000s
On-Board Storage	Micro SD slot, up to 256GB
Alarm	NA
Audio	1 input (RCA), 1 output (RCA)
Hardware Reset	Yes
Smart Feature	NA
Ethernet	RJ45(10/100BASE -T)
Video Compression Format	H.265/H.264
Resolution	Main Stream: 5 MP (2592*1944), 4 MP (2592x1520), 3 MP (2304x1296), @30fps, 1080P(1920x1080) @30fps, 960P(1280 x960) @ 30fps 720P (1280x 720) @ 30fps Sub Steam @20fps 720P(1280x720 ), VGA (640x480), QVGA (320x240) Mobile Stream @20fps QVGA (320x240)
Video Quality Adjustment	256Kbps ~ 8Mbps
Bitrate control method	CBR/VBR
Streaming Capability	Triple-Stream (Main/Sub/Mobile)
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Web browser	IE10/11, Safari V12.1 above, Firefox V.52 above, Google chrome V.57 above, Edge V.79 above
Security	IP address filter; complicated password; Authenticated username and password
Streaming Method	Unicast/Multicast
Application Programming Interface	ONVIF (Profile S/G/T)
Operating Conditions	-35 ~ +60°C/less than ≤ 95% RH
Ingress Protection	IP67
Input Voltage / Current	DI2V/POE(IEEE802.3af)
Power Consumption OFF)	2W -3W
Power Consumption ON)	6W -8W
Material	Metal
Dimensions (H x W x D)	242*87.4*83.88mm
Weight	782g

Your World is More Secure with us

### General Information

- 5MP Motorized Bullet IP Camera
- Motorized Lens: 2.7mm-13.5mm
- Support Built-In Audio
- 50m IR Distance
- IP67
- Support Built-In SD cards Upto 256GB

### Dimensions

