

XIS-6040SE



PRODUCT DESCRIPTION

The XIS-6040SE[™] is a uniquely mobile X-Ray Inspection System (XIS) featuring shock-absorbing wheels, stainless-steel handles, collapsible roller tables, a foldable screen and a spill resistant conveyor belt. The ideal package solution, the XIS-6040SE[™] is designed for special events, schools, and sports stadiums where effective threat detection requires power, mobility, and high throughput.

ABOUT ASTROPHYSICS

Since 2002, Astrophysics has led the industry in research and development, creating integrated solutions to advance the critical security missions of our customers and partners. Headquartered outside of Los Angeles, CA in the USA, Astrophysics has over 35,000 systems deployed in more than 150 countries, safeguarding critical infrastructure, aviation, and ports and border sites worldwide.

TOMORROW'S TECHNOLOGY FOR TODAY'S SECURITY™

XIS-6040SE[™]

GENERAL SPECIFICATIONS

60.0 cm × 40.0 cm 23.6″ × 15.8″
242.6 cm x 80.4 cm x 184.2 cm 95.5″ x 31.7″ x 72.5″
146.8 cm x 80.4 cm x 145.0 cm 57.8″ x 31.7″ x 57.1″
158.8 cm x 96.5 cm x 168.9 cm 62.5″ x 38.0″ x 66.5″
481 kg (1060 lbs)
522 kg (1150 lbs)
23 cm/s (45 ft/min) Forward or Reverse
165 kg (364 lbs) Evenly Distributed Load

X-RAY GENERATOR & IMAGE PERFORMANCE

Voltage:	160kV, Operating at 150kV
Tube Current:	0.7 mA
Wire Resolution:	40 AWG Typical, 38 AWG Standard
Steel Penetration: ²	39 mm Typical, 37 mm Standard
Cooling:	Sealed Di-Electric bath with Forced Air
Duty Cycle:	100%, No Warm-Up Procedure Required
Beam Direction:	Diagonally Upward

COMPUTER & VIDEO

Platform: Windows® 10 OS Memory: 8 GB RAM Storage: 256 GB SSD Display Type: **Display Resolution:** 1920 x 1200

24" Flat Panel Monitor

ENVIRONMENTAL

0°C to 40°C / 32°F to 104°F Operating Temperature: -20°C to 60°C / -4°F to 140°F Storage Temperature: Up to 95% Non-Condensing Humidity:

ELECTRICAL

System Power:	110VAC +/- 10% 50/60Hz, 15 Amp Max
	220 VAC +/- 10% 50/60Hz, 10 Amp Max
Power Conditioner:	Automatic Voltage Regulator (AVR), 600VA

HEALTH & SAFETY

Compliant with USFDA Center for Devices and Radiation Health Standards for Cabinet X-Ray Systems (21-CFR 1020.40) Typical radiation leakage is less than 0.1 mR/hr (Leakage less than 0.5 mR/hr permitted by U.S. Federal Standards)

180KV GENERATOR UPGRADE

Penetration²: 41 mm Steel Typical, 39 mm Standard

ISO 9001 & ISO 14001 CERTIFIED



¹Weight and dimensions of the system may vary depending on customization. ²As tested on Astrophysics Inc. Test Piece.

³Optional Features may affect lead time, price, and weight of product. Please contact your Astrophysics Sales Representative for more information.

Due to continued product development, Astrophysics Inc. reserves the right to amend all technical specifications without prior notice. Contact sales@astrophysicsinc.com for the most updated brochures.

Astrophysics HQ +1.909.598.5488 Astrophysics – EMEA +961.9.832.500

Astrophysics – INDIA +91.11.41709990

Astrophysics – ASIA +63.2.812.0033

809 mm / 31.9 in

OPTIONAL

FEATURES STANDARD

3 & 6 Color Imaging

Pseudo Color

Black & White Imaging

Reverse Monochrome

Material Discrimination

Auto Image Archiving

Image Review

Save Image (RGB)

Image Annotation JPEG Conversion

Print Image Capable Multi-Tier Accessibility Network Ready Real-Time Self Diagnostics

Baggage Counter Built-in Mobility Kit Built-in Roller Tables Liquid Catch Tray Conveyor

Continuous Scanning Continuous Zoom Up to 64x

. Vertical Zoom Panning

COMPACT STORAGE

Roller Bed 9 Quadrant Zoom

Enhanced Imaging[™] (EI)

High Penetration Function

Organic/Inorganic Imaging

Atomic Z-Number Measurement

Real-Time Image Manipulation

Geometric Image Distortion Correction

Artificial Intelligence (AI) Density Alert Local Language Safe Passage® Computer Based Training Screener Assist Software Threat Image Projection (TIP) Software

Conveyor Capacity Load Increase External USB Ports Variable Conveyor Speed

Custom Paint Environmental Kit Internal/External UPS Radiation Meter

1468 mn 57.8 in QUICK DEPLOYMENT 1842 mm 72 5 in

2426 mm 95.5 in

